



Nitrile

Black nitrile gloves that mask stains

- The distinctive color of these black nitrile gloves hides stains and provides contrast for improved visibility
- These disposable grip gloves feature a fully textured design for a confident grip



Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Machinery and Equipment
- Warehousing

Recommended For

- Inspection, selecting, checking parts
- General Purpose Auto Aftermarket
- Use of cleaning tools and robotic equipment
- Oil, fluids and filter change
- Engine transmission and repair
- Tire rotation & changes
- Maintaining lab furniture and equipment
- Sample taking and processing
- Blending, compounding solids and liquids
- Protection from Type I latex



TECHNICAL DATA SHEET

PRODUCT INFORMATION

	MidKnight® MK-296
Material	Nitrile
Color	Black
Glove Design	Chlorinated, Powder-Free, Silicone Free, Fully Textured
Cuff	Beaded
Manufacturing/QMS Audit Standards	ISO 13485:2003
Regulatory	ASTM D6319, EN 1149-1/2/3, EN 420:2003 + A1:2009, FDA21 CFR 177-2600-US Food Contact Approved, Food Type: Rubber, ISO 11193, US QSR/FDA 510(k) Medical Examination Grade
Packaging	100 gloves = 1 dispenser 10 dispensers = 1 case 1000 gloves = 1 case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition
Country of Origin	Malaysia
User Needs Segment	Robust
Available sizes	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
Anti-static	YES

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	245 / 9.6		ASTM D3767,EN420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.12 / 4.7		ASTM D3767,EN420
Finger Thickness (mm/mils)	0.15 / 6.0		ASTM D3767,EN420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	24	20	ASTM D412 & D573
Elongation at Break (%)	600	500	ASTM D412
Force at break (N)	7	6	EN 455-2